

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)


PCT

(10) International Publication Number
WO 2004/015555 A2

- (51) International Patent Classification⁷: **G06F 3/00** (74) Agents: CURRIER, T., Andrew et al.; LANG MICHENER, BCE PLACE, SUITE 2500, 181 BAY STREET, P.O. BOX 747 (CA).
- (21) International Application Number: PCT/CA2003/001179
- (22) International Filing Date: 8 August 2003 (08.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2,397,431 9 August 2002 (09.08.2002) CA
- (71) Applicant (for all designated States except US): XYZ INTERACTIVE TECHNOLOGIES INC. [CA/CA]; 989 LILLIAN STREET, TORONTO, Ontario M2M 3E8 (CA).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): LOHBIHLER, Andrew [CA/CA]; 989 LILLIAN STREET, TORONTO, Ontario M2M 3E8 (CA).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR POSITION SENSING



(57) Abstract: Embodiments of the present invention include one or more wireless transmitting devices and an array of receiver units for receiving wireless communications from the transmitting devices. The transmitter devices and receiver units can be arranged in one, two or three dimensional configurations. Signals are transmitted from the devices for identification and accurate location determination. Spread spectrum techniques can be used, such as DSSS, FHSS, THSS, and pseudo-noise (PN) coding schemes, or combinations thereof. The transmitting devices can generate one or a plurality of data signals that are orthogonal-code modulated, to be decoded by the receiver units and a processor associated therewith. A plurality of transmitter signals can be received, identified, located, and data demodulated substantially simultaneously using embodiments of the invention. The combined use of array processing methods and diversity schemes can be used to reduce the effects of signal multi-path and occlusion.

WO 2004/015555 A2



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.